

V01414

CARPET DEFOAMER CONCENTRATED FOAM CONTROL



Description

This highly concentrated product quickly penetrates and knocks down foam to eliminate problems associated with recovery tank foaming.

Product directions

Shake or mix container well before using.

Extractors or automatic scrubbers: Initially place 1 oz of defoamer per gallon capacity of the pick up tank (8 mL/L) 1:128. If carpet is full of shampoo from previous cleanings, more defoamer may be needed.

Sewage systems or water plants: Add defoamer, wait a few minutes for it to disperse, continue until suds subside.

First aid

If splashed in eyes, flush with large quantities of water. Call a physician if irritation persists. **If swallowed,** do not induce vomiting. Rinse out mouth with water. Call a physician.

To download current SDS information, please visit veritivcorp.msds.com.

Application

Recommended for use in recovery tanks of extraction machines or automatic scrubbers where foaming might be a problem.

Features/Benefits

Fast acting: breaks foam on contact

Saves time: eliminates downtime and wasted effort in dumping recovery tanks

Versatile: has many uses and can be used anywhere foaming is a problem

Specifications

Color: White

Scent: Characteristic

pH: 7 – 8

Dilution: 1:128

Density: 1

Packaging

V01414: 4/1 gal



© 2016 Veritiv Corporation. All rights reserved. Veritiv, the Veritiv logo, Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of the respective owners and are used herein for identification purposes only. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. RBCHTDS33651