



V01457, V01458

SUPER STRIP™ NON-AMMONIATED FLOOR STRIPPER



Description

This product quickly unlocks the molecular structure of all types of water-based floor finishes and sealers. This product also is an excellent heavy duty cleaner. It is great for cutting wax build-up, grease, oil and dirt. The unique chemical elements penetrate, dissolve and lift the wax to the surface to be picked up easily. This product is effective in hot, cold, hard or soft water. Safe for use on all floors not harmed by water.

Product directions

Pre-test in a small area. Bleed or discoloration may occur on rubber tile, or asphalt tile. Not recommended for strip linoleum or sheet vinyl floors. Sweep or dust mop floors or to remove any large debris. Dilute with hot water.

Normal strip: dilute 13 oz/gal or 100 mL/L (1:10) of water.

Heavy strip: dilute 25 oz/gal or 200 mL/L (1:5) of water.

Apply solution liberally to floors or surface. Allow 4 – 5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a low speed rotary machine, automatic scrubber or strip machine. Pick up solution with a wet vacuum, automatic scrubber or mop and bucket thoroughly. Rinse the floors or allow floors to dry completely before applying finish or sealer.

First aid

If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or physician. **If swallowed,** immediately call a poison center or physician. Rinse mouth. Do not induce vomiting. **If on skin (or hair),** take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a poison center or physician. **If in eyes,** rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or physician. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

To download current SDS information, please visit
veritivcorp.msds.com.

Application

Recommended for water-based acrylic and urethane fortified floors or finishes from all types of resilient tile and hard surfaces.

Features/Benefits

Extended suspension of emulsified particles eliminates costly restripping

Pleasant: no harsh ammonia or solvent odors

Powerful stripping action

Specifications

Color: Pink

Scent: Pleasant

pH: 13.0 – 14.0

Dilution: 1:5 – 1:10

Density: 1.075

Packaging

V01457: 4/1 gal

V01458: 5 gal BIB



© 2016 Veritiv Corporation. All rights reserved. Veritiv, the Veritiv logo, Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of the respective owners and are used herein for identification purposes only. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. RBCHTDS33651