



# V01448, V01449

## MAX STRENGTH FIRST TIME™ NON-AMMONIATED FLOOR STRIPPER



### Description

This fast-acting floor finish liquefier will solve stripping difficulties caused by frequent high speed burnishing, super hard urethane fortified finishes or excessive buildup. This product is designed to remove layers of floor finish in less time with less effort and no rinsing. Floors are ready to recoat without neutralizing when used as directed.

### Product directions

Sweep or dust mop the floor to remove any large debris. Dilute with warm to hot water.

For normal stripping, dilute 13 oz/gal or 100 mL/L (1:10) of water.

For heavy stripping, dilute 25 oz/gal or 200 mL/L (1:5) of water.

Apply solution liberally to floor surface. Allow a minimum of 5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a low-speed rotary machine, automatic scrubber or stripping machine. Pick up the solution with a wet vacuum, an automatic scrubber or a mop and bucket and thoroughly rinse the floor. Allow floor to dry completely before applying finish or sealer. No flood rinsing is necessary if surface appears free of dust and residue. Please recycle empty container.

### First aid

If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or physician. If swallowed, immediately call a poison center or physician. Rinse mouth. Do not induce vomiting. If on skin (or hair), take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a poison center or physician. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or physician.

To download current SDS information, please visit [veritivcorp.msds.com](http://veritivcorp.msds.com).

### Application

Recommended for removing water-based acrylic floor finishes from all types of resilient tile and hard surfaces. Pre-test in a small area; color bleeding or discoloration may occur on linoleum, rubber tile or asphalt tile. Not recommended for stripping linoleum or sheet vinyl floors.

### Features/Benefits

Powerful formula cuts through layers of old finish in minutes

Rinse free: no alkaline residue

Low foaming

### Specifications

Color: Slight amber

Scent: Pleasant

pH: 13.5 – 14.0

Dilution: 1:10, 1:5

Density: 1.045

### Packaging

V01449: 4/1 gal

V01448: 5 gal BIB



© 2016 Veritiv Corporation. All rights reserved. Veritiv, the Veritiv logo, Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of the respective owners and are used herein for identification purposes only. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. RBCHTDS33651