



V01452, V01453

OUTSTANDING™ UHS FLOOR FINISH



Description

Outstanding UHS Floor Finish is a highly repairable, low odor, black heel mark resistant floor finish. Designed for ultra high speed routine maintenance programs in high profile, high traffic areas; Outstanding provides a dramatic gloss response when burnished. Excellent leveling and low odor make it easy to apply.

Product directions

For restorative maintenance, completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 – 30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. A minimum of four coats of finish is recommended. **Note:** this product is a self-sealing finish; however, if tile is old, worn or porous, initially applying 1 – 2 coats of a sealer will enhance gloss and long term performance.

For routine maintenance, sweep large debris and dust mop. Damp mop or automatic scrub using a floor cleaner. Buff or burnish the floor to enhance gloss as needed. Use a restorer to condition the floor and extend the time between top scrub and recoating.

For interim maintenance, sweep large debris and dust mop the floor. Top scrub the floor using a daily cleaner and maroon pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 – 2 coats of finish as directed above.

First aid

If splashed in eyes, flush with large quantities of water. If irritation persists, call a physician. **If swallowed**, do not induce vomiting. Rinse out mouth with water. Call a physician.

To download current SDS information, please visit
veritivcorp.msds.com.

Application

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces.

Features/Benefits

Excellent off the mop gloss

Exceptional response to propane, battery or electric equipment

Extremely low odor

Superior black heel mark resistance

Specifications

Color: Opaque white

Scent: Characteristic

pH: 8.1 – 8.9

Dilution: RTU

Density: 1.02

Packaging

V01452: 4/1 gal

V01453: 5 gal BIB



© 2016 Veritiv Corporation. All rights reserved. Veritiv, the Veritiv logo, Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of the respective owners and are used herein for identification purposes only. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. RBCHTDS33651