



# V01450

## MIRRORSHINE™ ULTRA HIGH GLOSS FLOOR FINISH



### Description

This floor finish utilizes highly durable internally cross-linked polymers blended to achieve a harder floor finish film. This unique chemistry results in a high gloss, long wearing finish that cures faster and harder than any other metal-interlock finish. The perfect labor saving advantage for educational and retail facilities which have little or no time for floor burnishing.

### Product directions

**Restorative maintenance:** completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 – 30 minutes. Elevated temperatures and humidity may extend dry time. 4 – 5 coats of finish are recommended. **Note:** this product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 – 2 coats of a sealer will enhance gloss and long term performance.

**Routine maintenance:** sweep large debris and dust mop (using a water-based treatment). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating.

**Interim maintenance:** sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 – 2 coats of finish as directed above.

### First aid

If splashed in eyes, flush with large quantities of water. Call a physician if irritation persists. If swallowed, do not induce vomiting. Rinse out mouth with water. Call a physician.

To download current SDS information, please visit [veritivcorp.msds.com](http://veritivcorp.msds.com).

### Application

Recommended for use on all types of resilient tile (vinyl composition, vinyl, linoleum) and properly sealed hard surfaces (marble, terrazzo).

### Features/Benefits

- Superior wearing
- Resists dirt embedment
- Non-scutting
- Self-leveling, self-sealing
- 0.0% free styrene

### Specifications

- Color: Opaque white
- Scent: Characteristic
- pH: 8.1 – 8.9
- Dilution: RTU
- Density: 1.0265

### Packaging

V01450: 5 gal BIB



© 2016 Veritiv Corporation. All rights reserved. Veritiv, the Veritiv logo, Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of the respective owners and are used herein for identification purposes only. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. RBCHTDS33651