

V01451

MULTI-SURFACE SEALER PROTECTIVE COATING



Description

This water-based urethane sealer and finish revolutionizes the way hard surface floors are sealed. It can be applied effortlessly over new and old concrete, slate, quarry tile, terrazzo and marble and is resistant to a variety of chemicals. Ease of maintenance is exceptional and requires no etching before application.

Product directions

For restorative maintenance, completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 30 – 45 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. A minimum of four coats of finish is recommended.

For routine maintenance, sweep large debris and dust mop. Damp mop or automatic scrub using a floor cleaner. Buff or burnish the floor to enhance gloss as needed. Use a restorer to condition the floor and extend the time between top scrub and recoating.

For interim maintenance, sweep large debris and dust mop. Top scrub the floor using a cleaner and maroon pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 – 2 coats of finish as directed above. Please recycle empty containers.

For concrete application, may be applied to new concrete after 30 days (fully cured) and a surface temperature above 50°F. Prior to applying sealer to new concrete, use an acidic solution to neutralize excess alkalinity. All new concrete must be cleaned and rinsed. Not for use outdoors. Old concrete must be cleaned with a degreasing solution and rinsed for proper adhesion.

For glazed tile/polished surfaces, test in an inconspicuous area first, proper adhesion may be difficult due to lack of porosity.

First aid

If **splashed in eyes**, flush with large quantities of water. Call a physician if irritation persists. If **swallowed**, do not induce vomiting. Rinse out mouth with water. Call a physician.

To download current SDS information, please visit veritivcorp.msds.com.

Application

Recommended for use on all types of stone flooring (brick, marble, slate, terrazzo and concrete-new and old), resilient tile, quarry and non-glazed ceramic tile.

Features/Benefits

Versatile: adheres to a variety of hard surface floors

Long lasting: protection and abrasion resistance

Labor saving: high solids requires fewer coats

Specifications

Color: Opaque white

Scent: Characteristic

pH: 8.4 – 8.9

Dilution: RTU

Density: 1.03

Packaging

V01451: 5 gal BIB



© 2016 Veritiv Corporation. All rights reserved. Veritiv, the Veritiv logo, Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of the respective owners and are used herein for identification purposes only. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. RBCHTDS33651