



V02330, V02054, V02055, V02056, V02057 V03556, V03555, V03557



BLACK STRIPPING PAD

Description

The Black Stripping Pad is constructed of polyester fibers in an open textured, nonwoven fabrication. Abrasive particles are distributed throughout the pad and adhered to the nonwoven construction with a sturdy adhesive.

Directions for use

Dust mop or sweep floors prior to stripping. Use pad until soil and finish are removed from floor. Pick up stripping or cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic.

Construction

The Black Stripping Pad is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides.

Product care

To prolong the life of this product, it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

"Green" initiative

- The polyester fiber used in our pads comes from 100% post-consumer and industrial recycled waste products.
- Full Cycle® formulated to biodegrade* in a fraction of the time that it takes conventional floor pads once discarded into an active landfill.
- Water-based latex resins are used in the manufacturing process. No phenol-formaldehyde resins are used in our binding process.
- Shipping cartons contain at least 45% recycled material.
- Plant is operating under EPA approved Clean Air Permit.

* For complete details or to view ASTM D5511 test results visit fullcyclepads.com

Features/Benefits

Use with water-based floor stripping solution to remove worn and soiled floor finishes or sealers. May also be used to clean heavily soiled hard surface floors, such as concrete, when used with proper cleaning solutions. For use on standard electric floor machines or automatic scrubbers. Ideal for use with machine speeds up to 350 rpm.

Specifications

V03557: 12" dia
V02054: 13" dia
V03556: 14" dia
V03555: 16" dia
V02055: 17" dia
V02056: 19" dia
V02057: 20" dia
V02330: 14" x 20"
Center hole: 3.25"
Thickness: 0.94"
Weight: 48 osy
Fiber type: Recycled polyester
Binder system: Cross-linkable, water-based
Binder application: Spray/Dip
Abrasive application: Spray/Dip
Abrasive: Yes
Colour: Black
Green Seal™ certified

Packaging

5/Case



Full Cycle® Products are certified by Green Seal® for Environmental Innovation based on faster biodegradation in landfill conditions and 100% recycled content/natural fiber. GreenSeal.org/GS20

© 2018 Veritiv Corporation. Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of the respective owners and are used herein for identification purposes only. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. WF 160156

04/18
RBFHPadTDSCAEN