

V03334, V03335, V03336

LOW MAINTENANCE FLOOR FINISH



Description

This finish delivers both optimal value and performance and is developed specifically for facilities that desire to contain floor maintenance costs. Education and retail facilities will realize savings to their bottom line, while also meeting bid specifications. This formula is designed for low maintenance programs where burnishing is minimal or unavailable. Great off the mop gloss, quick build and superior leveling make this finish easy to apply.

Product Directions

For restorative maintenance, completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic mop finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20–30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. **Note:** This product is a self-sealing finish; however, if tile is old, worn or porous, initially applying 1–2 coats of a sealer will enhance gloss and long term performance. For routine maintenance, sweep large debris and dust mop. Damp mop or automatic scrub using a floor cleaner. Buff or burnish the floor to enhance gloss as needed. Use a restorer to condition the floor and extend the time between top scrub and recoating. For interim maintenance, sweep large debris and dust mop the floor. Top scrub the floor using a daily cleaner and applicable floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1–2 coats of finish as directed above. Refer to product SDS.

First Aid

Warning! Causes serious eye irritation. Wear eye or face protection. Wash hands thoroughly after handling. **Keep out of reach of children.**

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

Application

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces

Features/Benefits

- 25% high gloss finish
- Ideal for use in high traffic areas
- Easy to apply
- Reduces the number of coats required to obtain a high gloss finish
- Can be used on all types of flooring
- Does not yellow over time
- Black mark and stain resistant

Specifications

- Colour: White
- Scent: Characteristic
- pH: 8.5
- Dilution: RTU
- Density: 1.01

Packaging

- V03334: 4/4 L
- V03335: 2/10 L
- V03336: 20 L

© 2019 Veritiv Corporation. Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of the respective owners and are used herein for identification purposes only. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. WF 165610

04/19
RBChemTDSCAEN