

V05170

LOW MAINTENANCE FLOOR FINISH



Description

Low Maintenance Floor Finish is formulated to work with any maintenance method and equipment on all types of floors. It offers good gloss characteristics along with durability making it the number one choice of school boards and institutions where spray-buffing maintenance schedules and budgets are restricted. The product offers fast drying properties so down time is at a minimal and it responds well to burnishing.

Product Directions

Completely remove old finish and sealer from the floor using a floor stripper and rinse thoroughly. When floor is dry apply 2-3 uniform coats of finish. Allow 30 minutes drying time between coats.

Dry mopping: Remove loose dirt and grit with a dust mop. If required, apply 1-2 coats of a floor sealer.

Wet mopping: Use a neutral cleaner as directed.

Spray buffing: Ensure a minimum base of 2-3 coats of finish is on the floor. Use a 50-50 mixture of Low Maintenance Floor Finish.

Precautions for Food Plants:

Must be applied in keeping with manufacturers' recommendations for application on hard smooth level surfaces. To avert possible adverse organoleptic effects in food, which are processed in the area, adequate precautions should be taken to ensure that the volatile constituents of the applied products do not contaminate the foods.

Technical Specifications

Appearance: Opaque Liquid

Colour: White

Scent: Acrylic

Specific Gravity: 1.005 – 1.045

pH: 7.0 – 9.5

Refractive Index (% Brix): 22.0 – 24.0%

Coverage: 200 square meters/4 liters

© 2021 Veritiv Corporation. Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of their respective owners. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. WF393307

4/26
RBChemTDSCAEN