

V03332, V03333

PREMIUM UHS FLOOR FINISH



Description

Premium UHS Floor Finish is a highly repairable, black heel mark resistant floor finish. Designed for ultra speed routine maintenance programs in high profile, high traffic areas; Premium UHS Floor Finish provides a dramatic gloss response when burnished. Excellent leveling makes it easy to apply.

Product Directions

For restorative maintenance, completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic mop finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20–30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. **Note:** This product is a self-sealing finish; however, if tile is old, worn or porous, initially applying 1–2 coats of a sealer will enhance gloss and long term performance.

For routine maintenance, sweep large debris and dust mop. Damp mop or automatic scrub using a floor cleaner. Buff or burnish the floor to enhance gloss as needed. Use a restorer to condition the floor and extend the time between top scrub and recoating.

For interim maintenance, sweep large debris and dust mop the floor. Top scrub the floor using a daily cleaner and applicable floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1–2 coats of finish as directed above. Refer to product SDS.

First Aid

Warning! Causes serious eye irritation. Wear eye or face protection. Wash hands thoroughly after handling. **Keep out of reach of children.**

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **If eye irritation persists:** Get medical attention.

Application

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces

Features/Benefits

- 25% solids high gloss finish
- Delivers excellent gloss build
- Provides outstanding durability
- Dramatic response to propane, battery and electrical equipment
- Can be used on all types of flooring

Specifications

- Colour: White
- Scent: Characteristic
- pH: 8.5
- Dilution: RTU
- Density: 1.03

Packaging

- V03332: 4/4 L
- V03333: 2/10 L



PRODUCT CERTIFIED
FOR REDUCED
ENVIRONMENTAL
IMPACT. VIEW SPECIFIC
ATTRIBUTES EVALUATED:
UL.COM/EL
UL 2759

© 2019 Veritiv Corporation. Reliable Brand and the Reliable Brand logo are trademarks of Veritiv Corporation or its affiliates. All other trademarks are the property of the respective owners and are used herein for identification purposes only. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information. WF 165610

04/19
RBChemTDSCAEN